

NAME

snr; Tool for evaluating signal-to-noise-ratio (SNR) for speech signal.

USAGE

snr [-?] [-h] [-w <wlen>] [-s <wstep>] [-SNR] [-SSNR] [-SSNRA] [-LSNR <out>] <mixed> <clean> [-d <det>] [-E] [-v]

snr [-?] [-h] [-w <wlen>] [-s <wstep>] <-m num> [-SNR] [-SSNR] [-SSNRA] <noise> <clean> <mixed> [-d <det>] [-E] [-v]

snr [-?] [-h] [-w <wlen>] [-s <wstep>] [-SSNR] [-SSNRA] [-LSNR <out>] **-est1** <mixed> [-d <det>] [-E] [-v]

snr [-?] [-h] [-w <wlen>] [-s <wstep>] [-SSNR] [-SSNRA] [-LSNR <out>] **-est2** <mixed> [-d <det>] [-N <order>] [-E] [-v]

snr [-?] [-h] [-w <wlen>] [-s <wstep>] [-SSNR] [-SSNRA] **-estm** <mixed> [-L <t>] [-c <const>] [-fs <frequency>] [-d <det>] [-E] [-v]

snr [-?] [-h] **-LSNR** <out> **-estm** <mixed> [-L <t>] [-c <const>] [-fs <frequency>] [-v]

snr [-?] [-h] [-w <wlen>] [-s <wstep>] **-est** <mixed> [-d <det>] [-D <vad>] [-E] [-v]

DESCRIPTION

You can use program **snr** for evaluating **SNR** (Global SNR), **SSNR** (Segmental SNR), **SSNRA** (Arithmetic SNR), and **LSNR** (Local SNR). You can choose reverse process, generating mix file with demand signal-to-noise-ratio. In both case is possible to use an external detector of speech activity (VAD). If is not used external file with speech activity, program will use internal detector based in cepstral distance. If You use option [-E], internal detector based in energy algorithm will be used. The third usage of this tool is estimating SNR from one mixed signal without reference according to selected option (**SNR**, **SSNR**, **SSNRA**, **LSNR**). Evaluations are based on algorithms described in following publications:

- 1) P. Pollak: Estimation Methods of Speech SNR, Metody odhadu odstupu signalu odsumu v recovem signalu (Czech language) In Akusticke listy, Vol. 7, 2001
- 2) P. Pollak: Efficient and Reliable Measurement and simulations of noisy speech background, In EUSPICO 2002, Sep 2002
- 3) J. Slezak: Urcovani pomeru signal-sum, SNR kriteria (Czech language). CTU, Prague 2001

MANDATORY PARAMETERS

<mixed>

Name of the file with the noisy speech. (required parametr)

<clean>

Name of the file with the clean speech. (required parametr)

<noise>

Name of the file with the noise signal. (required parametr)

OPTIONAL PARAMETERS

-d <det>

Usage of external detector VAD, <det> is required name of the text file with speach activity.

-D <vad>

Usage of external detector on the sample level, <vad> is required name of the text file with speach activity.

-E Usage of internal detector VAD based in energy algorithm.

-SNR Usage for evaluation of global signal-to-noise-ratio. (**SNR**)

-SSNR Usage for evaluation of segmental signal-to-noise-ratio. (**SSNR**)

-SSNRA

Usage for modified evaluation of segmental signal-to-noise-ratio. (**SSNRA**)

-LSNR <out>

Usage for evaluation of local signal-to-noise-ratio. <out> is required name of the out file.

-h, -? Prints the help and exits.

-w <wlen>

Set the segment window length. Must be positiv. Defalt value is 512.

-s <wstep>

Step of the window beginnings. Default is 256. (50% overlaping)

-m <num>

Option for generating mixed file with demand (*num*) signal-to-noise-ratio.

-N <order>

Order of running average, default is N=10.

-L <t>

Time interval in sec for Martin algorithm, default is t=0.5.

-c <const>

Multiple constant for Martin algorithm, default is c=1.2.

-fs <frequency>

Sampling frequency in Hz, default is fs=8000.

-est1 First estimation method of evaluating signal-to-noise-ratio. It is based in averaging of the energy of the noise backgrounds.

-est2 Other estimation method of evaluating signal-to-noise-ratio. It is based in running average.

-estm Martin estimation method of evaluating signal-to-noise-ratio. It is based in founding of minimum power in interval **L**.

-v Verbose abstract.

EXAMPLES

snr -w 512 -s 512 -SNR mixed_speech.bin clean_speech.bin -d detector.det

Return **SNR** in dB of signal-to-noise-ratio with length of segment 512 samples and step 512 samples. Tool use external detector of speech activity.

snr -SSNRA mixed_speech.bin clean_speech.bin

Return **SSNRA** in dB of signal-to-noise-ratio with length of segment 512 samples and step 256 samples. Tool use internal detector of speech activity based in cepstral distance.

snr -SSNRA -m 0 noise.bin clean_speech.bin mixed_speech.bin -E

In file *mixed_speech.bin* tool return mixed signal with 0 dB of **SSNRA** signal-to-noise-ratio. Length of segment is 512 samples and step 256 samples. Program will use internal detector of speech based in energy algorithm.

snr -w 512 -s 512 -LSNR output.txt mixed_speech.bin clean_bin -d detector.det

In file *output.txt* tool return for each segment the **LSNR** signal-to-noise-ratio. Tool use external detector of speech activity. Length of segment is 512 samples and step 512 samples.

snr -SSNR -est1 mixed_file.bin

Return **SSNR** in dB of signal-to-noise-ratio with length of segment 512 samples and step 256 samples. Tool use estimation method based in exponential forgetting and internal detector of speech activity.

snr -w 256 -s 256 -SSNR -est1 mixed_file.bin -d detector.det

Return **SSNR** in dB of signal-to-noise-ratio with length of segment 256 samples and step 256 samples. Tool use estimation method based in exponential forgettery and external detector of speech activity.

snr -SSNR -est2 *mixed_file.bin* **-d** *detector.det*

Return **SSNR** in dB of signal-to-noise-ratio with length of segment 512 samples and step 256 samples. Tool use estimation method based in running average. Tool use external detector of speech activity.

snr -SSNRA -estm *mixed_file.bin* **-L 0.8 -fs 8000**

Return **SSNRA** in dB of signal-to-noise-ratio with length of segment 512 samples and step 256 samples. Tool use Martin algorithm with time interval 0.8 s and sample frequency 8000 Hz

AUTOR

Martin Vondrasek, CVUT FEL K331

vondram3@feld.cvut.cz, pollak@feld.cvut.cz

Version 4.1 26.11.2003